



Chamäleon GmbH
Rudolf-Diesel-Straße, 8a
69115 Heidelberg-Germany
Tel.: +49-(0)-6221 520440
Fax: +49-(0)-6221 520449
E-mail: info@chamaeleon/produktion.de
<http://www.chamaeleon/produktion.de>

TECHNICAL DATA SHEET

CHAMÄLEON SPOT BLENDER

Article number:	13405
Intended use:	Car refinishing Product/ Preparation
General characteristics:	Special solvent mixture to be used for dissolving spray dust at spot repairs and add-on paintings.
Recommended for:	Chamäleon 103, 133, 105, 155, 106, or similar 2K acrylic clear or base coats.

Usage:

After applying one of the above paints, spray immediately CHAMÄLEON SPOT BLENDER on the stained surfaces. After 10 - 15 seconds dissolve the spray dust with CHAMÄLEON SPOT BLENDER.

Remarks:

Do not use on thermoplastic acryls.

Storage: At least 4 years if stored tightly closed in original containers.

All products should be disposed of in relation to the regulations of the environmental health authorities. Protect your Environment!

For the additional information that is not included to the Technical Data Sheet apply to the supplier:

e-mail: info@chamaeleon-produktion.de

See information on safety in Safety Data Sheet.